



| | | |
|--------------------------------------|--|---|
| Machine type | | Mono Laser Digital Copier |
| Available functions | | Copy, Print and Scan |
| Copier | | |
| Copy speed | | Up to 22 cpm (A4) |
| First Copy Output Time (FCOT) | | Approx. 9 seconds or less |
| Copy resolution | | Up to 600 x 600 dpi |
| Copy modes | | Text, Text/Photo, Text/Photo+, Photo |
| Double sided copying | | 1-sided to 2-sided (Manual) |
| Multiple copy | | Up to 99 copies |
| Reduction / Enlargement | | 50-200% in 1% increments |
| Toner saver mode | | Yes |
| Other features | | Automatic & Manual Exposure, Collate, 2 on 1, ID Card Copy |
| Printer | | |
| Print speed | | Up to 22 ppm (A4) |
| Printing method | | Monochrome laser beam printing |
| Print quality | | Up to 1200 x 600 dpi with Automatic Image Refinement |
| Print resolution | | 600 x 600 dpi |
| Double sided printing | | Automatic |
| Printer languages | | UFRII-LT |
| Print margins | | 6 mm-top and bottom, 5 mm-left and right |
| Toner saver mode | | Yes |
| Scanner | | |
| Type | | Colour |
| Scan resolution | | Optical: Up to 600 x 1200 dpi Enhanced: Up to 9600 x 9600 dpi |
| Colour scanning depth | | 24 bit/24 bit (input/output) |
| Greyscales | | 256 levels |
| Compatibility | | TWAIN, WIA |
| Max. scan width | | 216 mm |
| Media handling | | |
| Scanner type | | Flatbed and Automatic Document Feeder (ADF) |
| Paper input (Standard) | | 250-sheet tray 1-sheet manual feed slot 35-sheet ADF |
| Paper output | | 100-sheet |
| Media types | | Plain paper, Heavy paper, Recycled paper, Transparency, Label, Envelope, |
| Media sizes | | Tray: A4, B5, A5, Executive, Envelope (COM10, Monarch, DL, ISO-C5), LTR, LGL, Custom sizes: Width 76 to 216 mm; Length 127 to 356 mm. Manual feed slot: A4, B5, A5, Executive, Envelope (COM10, Monarch, DL, ISO-C5), LTR, LGL, Custom sizes: Width 76 to 216 mm; Length 127 to 356 mm. ADF: A4, A5, Legal, Letter, Custom (W x L): Max 216 x 356 mm Min 105 x 148.5 mm. |

| | |
|--------------------------------------|--|
| Media weights | Tray: 64 to 128 g/m ² Manual feed slot: 64 to 163 g/m ² ADF: 40 to 105 g/m ² |
| Interface & Software | |
| Interface type | USB 2.0 Hi-speed |
| Operating System compatibility | Windows 2000/ XP/ Vista/ 7 Mac OS X version 10.4.9-10.6.x ¹ Linux ¹ |
| Software and printer management | Presto! Page Manager, MF Toolbox |
| General features | |
| Warm-up Time | Approx. 10 seconds from power on |
| Memory | 32 MB (shared) |
| Control panel | 16 characters x 2 lines backlit LCD |
| Dimensions with trays (W x D x H) | 390 mm x 432 mm x 455 mm |
| Installation space (W x D x H) | 390 mm x 813 mm x 588 mm |
| Weight | Approx 12.75 Kg |
| Operating environment | Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) |
| Power Source | 220-240 V (±10%), 50/60 Hz (±2 Hz) |
| Power Consumption | Maximum: Approx. less than 650 W Standby: Approx. less than 9 W Sleep mode: Approx. 3 W Typical Electricity Consumption (TEC): 0.872 kWh/week |
| Noise Levels | Sound Pressure ² Active: 63.5 dB(A) or less Standby: Inaudible |
| Consumables | |
| Cartridges | Cartridge FX10 (2,000 pages ³) |
| Standard disclaimers | |
| [1] | Web distribution only |
| [2] | Declared noise emission in accordance with ISO 9296 |
| [3] | Based on 5% coverage (A4) |